

170-03093



Article Number: 170-03093

Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 250.0 ft/Bulk Reel



Base Data

Local Order Number 170-03093

Type BSPFR100B

Color Black (BK)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Open Post Termination No

Short Description Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 250.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 250.0 ft

Length L (metric) 76.2 m

Bundle Diameter min (imperial) 0.625 "

Bundle Diameter min (metric) 15.9 mm

Bundle Diameter max (imperial) 1.625 "

Bundle Diameter max (metric) 41.3 mm

Nominal Diameter (imperial) 1.0 "

Nominal Diameter (metric) 25.4 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 250 ft

Package Quantity 250.0 ft

Reel Length (imperial) 250.0 ft

Reel Length (metric) 76.2 m

Weight (imperial) 3.4 lbs

Weight (Metric) 1.5 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability VW-1

Mil-202
FAR 25
FMVSS 302

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

Certification / Specification UL94

UL Recognized (US and Canada) Yes