

170-03113



Article Number: 170-03113

Plenum Rated Expandable Braided Sleeving (Halar), 1.75" Dia., White, 30.0 ft/Reel

 RoHS

Base Data

Local Order Number	170-03113
Type	BSHLR13410
Color	White (WH)
Features and Benefits	• Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications. • Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation. • Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
Open Post Termination	No
Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 1.75" Dia., White, 30.0 ft/Reel

Product Dimensions

Length L (imperial)	30.0 "
Length L (metric)	9.1 mm
Width W (imperial)	0.02 "
Width W (metric)	.60 mm
Bundle Diameter min (imperial)	1.25 "
Bundle Diameter min (metric)	31.8 mm
Bundle Diameter max (imperial)	2.75 "
Bundle Diameter max (metric)	69.9 mm
Nominal Diameter (imperial)	1.75 "
Nominal Diameter (metric)	44.4 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	30 ft
Reel Length (imperial)	30.0 ft
Reel Length (metric)	9.1 m
Weight (imperial)	1.32 lbs

Material and Specifications

Material	Polyamide 6.6 (E/CTFE)
Material Shortcut	E/TFE
Flammability	FAR 25 UL VW-1

Melting Point	+250 °C
Operating Temperature	-103 °F to +302 °F (-75 °C to +150 °C)
ROHS Conformity	Yes
Certification / Specification	UL2024
UL Recognized (US and Canada)	Yes