

170-03115



**Article Number:** 170-03115

**Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia., White, 50.0 ft/Reels**



## Base Data

**Local Order Number** 170-03115

**Type** BSHLR2010

**Color** White (WH)

**Features and Benefits**

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

**Product Description** Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.

**Open Post Termination** No

**Short Description** Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia., White, 50.0 ft/Reels

## Product Dimensions

**Length L (imperial)** 50.0 ft

**Length L (metric)** 15.2 m

**Bundle Diameter min (imperial)** 1.5 "

**Bundle Diameter min (metric)** 38.1 mm

**Bundle Diameter max (imperial)** 3.5 "

**Bundle Diameter max (metric)** 88.9 mm

**Nominal Diameter (imperial)** 2.0 "

**Nominal Diameter (metric)** 50.8 mm

## Logistics and Packaging

**Quantity per** reel

**Package Quantity (imperial)** 50 ft

**Reel Length (imperial)** 50.0 ft

**Reel Length (metric)** 15.2 m

**Weight (imperial)** 2.3 lbs

**Weight (Metric)** 1.04 kg

## Material and Specifications

**Material** Polyamide 6.6 (E/CTFE)

**Material Shortcut** E/TFE

**Flammability** FAR 25  
UL VW-1

**Melting Point** +250 °C

**Operating Temperature** -103 °F to +302 °F (-75 °C to +150 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL2024

**UL Recognized (US and Canada)** Yes