

170-03124



Article Number: 170-03124

Split Wrap Braided Sleeveing, 0.13" ID, PET, Black, 400.0 ft/Bulk Reel



## Base Data

Local Order Number 170-03124

Type BSPSW180B

Color Black (BK)

**Features and Benefits**

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Product Description** A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Split Wrap Braided Sleeveing, 0.13" ID, PET, Black, 400.0 ft/Bulk Reel

## Product Dimensions

Length L (imperial) 400.0 ft

Length L (metric) 121.9 m

Bundle Diameter max (imperial) 0.13 "

Bundle Diameter max (metric) 3.0 mm

Nominal Diameter (imperial) 0.125 "

Nominal Diameter (metric) 3.2 mm

## Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 400 ft

Package Quantity 400.0 ft

Reel Length (metric) 121.9 m

Reel Length (imperial) 400.0 ft

Weight (imperial) 0.8 lbs

Weight (Metric) 0.36 kg

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes