

170-03127



Article Number: 170-03127

Split Wrap Braided Sleeving, 0.75" ID, PET, Black, 100.0 ft/Bulk Reel

 RoHS

Base Data

Local Order Number	170-03127
Type	BSPSW340B
Color	Black (BK)
Features and Benefits	• Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. • Unique construction retains shape and rigidity throughout unrolling. • Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
Product Description	A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Open Post Termination	No
Short Description	Split Wrap Braided Sleeving, 0.75" ID, PET, Black, 100.0 ft/Bulk Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Bundle Diameter max (imperial)	0.75 "
Bundle Diameter max (metric)	19.1 mm
Nominal Diameter (imperial)	0.75 "
Nominal Diameter (metric)	19.1 mm

Logistics and Packaging

Quantity per	box
Package Quantity (imperial)	100 ft
Reel Length (metric)	30.5 m
Reel Length (imperial)	100.0 ft
Weight (imperial)	1.6 lbs
Weight (Metric)	0.73 kg

Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL94 V0
Melting Point	+250 °C
Operating Temperature	-94 °F to +257 °F (-70 °C to +125 °C)
ROHS Conformity	Yes

