

170-03134



Article Number: 170-03134

Split Wrap Braided Sleeving, 0.5" ID, PET, Black, 1,200.0 ft/Large Bulk Reel

 RoHS

Base Data

|                       |                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number    | 170-03134                                                                                                                                                                                                                                                                                                                                                                                        |
| Type                  | BSPSW120LB                                                                                                                                                                                                                                                                                                                                                                                       |
| Color                 | Black (BK)                                                                                                                                                                                                                                                                                                                                                                                       |
| Features and Benefits | <ul style="list-style-type: none"><li>• Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li><li>• Unique construction retains shape and rigidity throughout unrolling.</li><li>• Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li></ul> |
| Product Description   | A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.                                                        |
| Open Post Termination | No                                                                                                                                                                                                                                                                                                                                                                                               |
| Short Description     | Split Wrap Braided Sleeving, 0.5" ID, PET, Black, 1,200.0 ft/Large Bulk Reel                                                                                                                                                                                                                                                                                                                     |

Product Dimensions

|                                |           |
|--------------------------------|-----------|
| Length L (imperial)            | 1200.0 ft |
| Length L (metric)              | 365.8 m   |
| Bundle Diameter max (imperial) | 0.5 "     |
| Bundle Diameter max (metric)   | 12.7 mm   |
| Nominal Diameter (imperial)    | 0.5 "     |
| Nominal Diameter (metric)      | 12.7 mm   |

Logistics and Packaging

|                             |           |
|-----------------------------|-----------|
| Quantity per                | reel      |
| Package Quantity (imperial) | 1200 ft   |
| Package Quantity            | 1200.0 ft |
| Reel Length (metric)        | 365.8 m   |
| Reel Length (imperial)      | 1200.0 ft |
| Weight (imperial)           | 12.0 lbs  |
| Weight (Metric)             | 5.4 kg    |

Material and Specifications

|                       |                                       |
|-----------------------|---------------------------------------|
| Material              | Polyester (PET)                       |
| Material Shortcut     | PET                                   |
| Flammability          | UL94 V0                               |
| Melting Point         | +250 °C                               |
| Operating Temperature | -94 °F to +257 °F (-70 °C to +125 °C) |

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes