

170-03141



Article Number: 170-03141

Flame Retardant Split Wrap Braided Sleeving, 0.25" ID, Black, 200.0 ft/Bulk Reel



Base Data

Local Order Number 170-03141

Type BSSWFR140B

Color Black (BK)

- Features and Benefits**
- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
 - Unique construction retains shape and rigidity throughout unrolling.
 - Self extinguishing product complies with UL VW-1 standards for flame resistant applications.
 - Easy open design allows quick assembly, future access, and ability to apply protective sleeving post installation.

Product Description A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Flame Retardant Split Wrap Braided Sleeving, 0.25" ID, Black, 200.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 200.0 ft

Length L (metric) 61.0 m

Bundle Diameter max (imperial) 0.25 "

Bundle Diameter max (metric) 6.4 mm

Nominal Diameter (imperial) 0.25 "

Nominal Diameter (metric) 6.4 mm

Logistics and Packaging

Quantity per box

Package Quantity (imperial) 200 ft

Package Quantity 200.0 ft

Reel Length (metric) 61.0 m

Reel Length (imperial) 200.0 ft

Weight (imperial) 1.2 lbs

Weight (Metric) 0.54 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability VW-1
FAR 25

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes

UL Recognized (US) Yes