

170-03143



**Article Number:** 170-03143

**Flame Retardant Split Wrap Braided Sleeving, 0.75" ID, Black, 100.0 ft/Bulk Reel**



## Base Data

**Local Order Number** 170-03143

**Type** BSSWFR340B

**Color** Black (BK)

- Features and Benefits**
- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
  - Unique construction retains shape and rigidity throughout unrolling.
  - Self extinguishing product complies with UL VW-1 standards for flame resistant applications.
  - Easy open design allows quick assembly, future access, and ability to apply protective sleeving post installation.

**Product Description** A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

**Open Post Termination** No

**Short Description** Flame Retardant Split Wrap Braided Sleeving, 0.75" ID, Black, 100.0 ft/Bulk Reel

## Product Dimensions

**Length L (imperial)** 100.0 ft

**Length L (metric)** 30.48 m

**Bundle Diameter min (imperial)** 19.1 "

**Bundle Diameter max (imperial)** 0.75 "

**Bundle Diameter max (metric)** 19.1 mm

**Nominal Diameter (imperial)** 0.75 "

**Nominal Diameter (metric)** 19.1 mm

## Logistics and Packaging

**Quantity per** box

**Package Quantity (imperial)** 100 ft

**Package Quantity** 100.0 ft

**Reel Length (metric)** 30.5 m

**Reel Length (imperial)** 100.0 ft

**Weight (imperial)** 1.6 lbs

**Weight (Metric)** 0.73 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** FAR 25  
VW-1

**Operating Temperature** -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes