

170-03147



Article Number: 170-03147

Flame Retardant Split Wrap Braided Sleeving, 2.0" ID, Black, 50.0 ft/Bulk Reel



Base Data

Local Order Number 170-03147

Type BSSWFR200B

Color Black (BK)

- Features and Benefits**
- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
 - Unique construction retains shape and rigidity throughout unrolling.
 - Self extinguishing product complies with UL VW-1 standards for flame resistant applications.
 - Easy open design allows quick assembly, future access, and ability to apply protective sleeving post installation.

Product Description A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Flame Retardant Split Wrap Braided Sleeving, 2.0" ID, Black, 50.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 50.0 ft

Length L (metric) 15.2 m

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.8 mm

Nominal Diameter (imperial) 2.0 "

Nominal Diameter (metric) 50.8 mm

Logistics and Packaging

Quantity per box

Package Quantity (imperial) 50 ft

Reel Length (metric) 15.2 m

Reel Length (imperial) 50.0 ft

Weight (imperial) 1.8 lbs

Weight (Metric) 0.82 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability VW-1
FAR 25

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes