

170-03157



Article Number: 170-03157

Flame Retardant Hook & Loop Braided Sleeving, 2.5", PET, Black, 100 ft/Bulk Reel

 RoHS

Base Data

Local Order Number	170-03157
Type	BSHKLPR212B
Color	Black (BK)
Features and Benefits	• Flexible construction that conforms to irregular shapes and contours. • Hook and loop feature wraps over cable bundle and allows future access to cables. • Easy access saves assembly time and allows for easy splicing or insertion of additional wires. • UL VW-1 rating for applications requiring high degree of flammability protection.
Product Description	Flame retardant expandable braided sleeving with hook & loop strip for wrapping around cable assemblies. Color matched hook & loop closure provides an easy on and off installation, as well as convenient access for harness break-outs.
Open Post Termination	No
Short Description	Flame Retardant Hook & Loop Braided Sleeving, 2.5", PET, Black, 100 ft/Bulk Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Bundle Diameter max (imperial)	2.5 "
Bundle Diameter max (metric)	63.5 mm
Nominal Diameter (imperial)	2.5 "
Nominal Diameter (metric)	63.5 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	100.0 ft
Reel Length (metric)	30.5 m
Reel Length (imperial)	100.0 ft
Weight (imperial)	3.75 lbs
Weight (Metric)	1.70 kg

Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Flammability	VW-1
Melting Point	+250 °C
Operating Temperature	-94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

Certification / Specification MIL-STD-202 VW-1