

# HellermannTyton

## 170-03191

**Article Number:** 170-03191

**Aluminum Laminated Fiberglass Wrap,4-FT Stick, 3/8" Dia., Silver, 30/Box**



Download spec sheet



Download tech sheet

### Base Data

**Local Order Number** 170-03191

**Type** BSHTTSW38SB

**Color** Silver (SR)

**Features and Benefits**

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

**Product Description** Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.

**Open Post Termination** No

**Short Description** Aluminum Laminated Fiberglass Wrap,4-FT Stick, 3/8" Dia., Silver, 30/Box

### Product Dimensions

**Length L (imperial)** 4.0 ft

**Length L (metric)** 1.22 m

**Diameter D (imperial)** 0.37 "

**Diameter D (metric)** 9.40 mm

**Nominal Diameter (imperial)** 3/8 "

**Nominal Diameter (metric)** 9.40 mm

**Wall Thickness WT (imperial)** 0.042 "

**Wall Thickness WT (metric)** 1.06 mm

### Logistics and Packaging

**Quantity per** box

**Package Quantity (imperial)** 30

**Package Quantity** 30

### Material and Specifications

**Material** Glass Fiber with aluminium foil (GF-AL)

**Material Shortcut** GF-AL

**Flammability** non flammable

**Operating Temperature** -76°F to +491°F (-60°C to +255°C)

**ROHS Conformity** Yes

---

© HellermannTyton 2014