

HellermannTyton

170-03201

Article Number: 170-03201

Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 1" Dia., AL; GF, Silver, 30/Box



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03201

Type BSHTTSW1LB

Color Silver (SR)

Features and Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.

Open Post Termination No

Short Description Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 1" Dia., AL; GF, Silver, 30/Box

Product Dimensions

Length L (imperial) 4.0 ft

Length L (metric) 1.22 m

Diameter D (imperial) 1 "

Diameter D (metric) 25.40 mm

Nominal Diameter (imperial) 1 "

Nominal Diameter (metric) 25.40 mm

Wall Thickness WT (imperial) 0.042 "

Wall Thickness WT (metric) 1.06 mm

Logistics and Packaging

Quantity per box

Package Quantity (imperial) 30

Package Quantity 30

Material and Specifications

Material Glass Fiber with aluminium foil (GF-AL)

Material Shortcut GF-AL

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Conformity Yes

© HellermannTyton 2014