

181-00232



Article Number: 181-00232

High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, White, 120ft/Carton



Base Data

Local Order Number 181-00232

Type SLHD2.5X3

Color White (WH)

- Features and Benefits**
- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
 - Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
 - Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 2.5 "

Width W (metric) 63.5 mm

Width W2 (imperial) 2.5 "

Width W2 (metric) 63.5 mm

Width W3 (imperial) 0.16 "

Width W3 (metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.16 mm

Width W5 (imperial) 2.6 "

Width W5 (metric) 66.04 mm

Width W6 (imperial) 0.75 "

Width W6 (metric) 19.05 mm

Height H (imperial) 3.0 "

Height H (metric) 76.2 mm

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 120

Package Quantity 36.6 m

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)
ROHS Conformity	Yes
UL Recognized (US)	Yes