

181-00456



Article Number: 181-00456

Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, White, 120ft/Carton

 RoHS

Base Data

Local Order Number	181-00456
Type	SD.75X75
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"><li>• A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li><li>• Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li><li>• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li></ul>
Product Description	HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (imperial)	6.0 ft
Length L (metric)	1.83 m
Width W (imperial)	1.5 "
Width W (metric)	38.1 mm
Width W2 (imperial)	1.5 "
Width W2 (metric)	38.1 mm
Height H (imperial)	1.05 "
Height H (metric)	26.7 mm
Mounting Hole Centers (imperial)	4.0 "
Mounting Hole Centers (metric)	101.6 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	120 ft
Package Quantity	120
Carton Quantity	120

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)

<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	CSA UL
<b>UL Recognized (US)</b>	Yes