

181-00603

Article Number: 181-00603

High Density Slotted Wall Wiring Duct, 1.5" X 1.5", Non-Adhesive, PVC, Black, 120ft/Carton

HellermannTyton



## Base Data

Local Order Number 181-00603

Type SLHD1.5X1.5

Color Black (BK)

- Features and Benefits**
- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
  - Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
  - Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 1.5" X 1.5", Non-Adhesive, PVC, Black, 120ft/Carton

## Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 1.52 "

Width W (metric) 38.6 mm

Width W2 (imperial) 1.5 "

Width W2 (metric) 38.1 mm

Width W3 (imperial) 0.16 "

Width W3 (metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 1.19 "

Width W5 (metric) 30.2 mm

Height H (imperial) 1.56 "

Height H (metric) 39.6 mm

Mounting Hole Centers (imperial) 2.0 "

Mounting Hole Centers (metric) 50.8 mm

## Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 120 ft

Package Quantity 36.6 m

Carton Quantity 120 ft

## Material and Specifications

---

<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC
<b>Flammability</b>	self-extinguishing
<b>Operating Temperature</b>	+122 °F (+50 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL CSA
<b>UL Recognized (US)</b>	Yes