

181-00619

Article Number: 181-00619

High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, Black, 120ft/Carton

HellermannTyton



Base Data

Local Order Number 181-00619

Type SLHD4X4

Color Black (BK)

- Features and Benefits**
- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
 - Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
 - Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, Black, 120ft/Carton

Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 4.0 "

Width W (metric) 101.6 mm

Width W2 (imperial) 4.0 "

Width W2 (metric) 101.6 mm

Width W3 (imperial) 0.16 "

Width W3 (metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 3.6 "

Width W5 (metric) 91.4 mm

Width W6 (imperial) 1.5 "

Width W6 (metric) 38.1 mm

Height H (imperial) 4.06 "

Height H (metric) 103.1 mm

Mounting Hole Centers (imperial) 2.0 "

Mounting Hole Centers (metric) 50.80 mm

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 120 ft

Package Quantity 36.6 m

Carton Quantity 120 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122 °F (+50 °C)

ROHS Conformity Yes

Certification / Specification CSA
UL

UL Recognized (US) Yes