

181-11000



Article Number: 181-11000

Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Black, 120ft/Carton

 RoHS

Base Data

Local Order Number	181-11000
Type	SD1X1
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.• Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Black, 120ft/Carton

Product Dimensions

Length L (imperial)	6.0 ft
Length L (metric)	1.83 m
Width W (imperial)	1.0 "
Width W (metric)	25.4 mm
Width W2 (imperial)	1.0 "
Width W2 (metric)	25.4 mm
Height H (imperial)	1.05 "
Height H (metric)	26.7 mm
Mounting Hole Centers (imperial)	4.0 "
Mounting Hole Centers (metric)	101.6 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	120 ft
Package Quantity	120
Carton Quantity	120

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
CSA Certified	Yes

Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)
ROHS Conformity	Yes
Certification / Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes