

181-12007

Article Number: 181-12007

Slotted Wall Wiring Duct, 1" X 2", Non-Adhesive, PVC, White, 30ft/Box



Base Data

Local Order Number	181-12007
Type	SL1X2
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none">• Strong fingers prevent unwanted breaking.• Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.• Restricted opening design in the finger of the duct helps keep wires in place.• Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".
Short Description	Slotted Wall Wiring Duct, 1" X2", Non-Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (imperial)	6.0 ft
Length L (metric)	1.83 m
Width W (imperial)	1.03 "
Width W (metric)	26.16 mm
Width W2 (imperial)	1.0 "
Width W2 (metric)	25.4 mm
Width W3 (imperial)	0.4 "
Width W3 (metric)	10.16 mm
Width W4 (imperial)	1.0 "
Width W4 (metric)	25.4 mm
Width W5 (imperial)	1.62 "
Width W5 (metric)	41.1 mm
Height H (imperial)	2.06 "
Height H (metric)	52.32 mm
Mounting Hole Centers (imperial)	4.0 "
Mounting Hole Centers (metric)	101.6 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	120 ft
Package Quantity	36.6 m
Carton Quantity	120

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
CSA Certified	Yes
Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)
ROHS Conformity	Yes
Certification / Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes
UL Recognized (US)	Yes