# HellermannTyton

# 181-42002



Article Number: 181-42002

Solid Wall Wiring Duct, 4" X 2", Non-Adhesive, PVC, Gray, 120ft/Carton

RoHS

## Base Data

Local Order Number	181-42002
Туре	SD4X2
Color	Gray (GY)
Features and Benefits	<ul> <li>A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li> <li>Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul>
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, 4" X2", Non-Adhesive, PVC, Gray, 120ft/Carton

## **Product Dimensions**

Length L (imperial)	6.0 ft
Length L (metric)	1.83 m
Width W (imperial)	4.03 "
Width W (metric)	102.4 mm
Width W2 (imperial)	4.0 "
Width W2 (metric)	101.6 mm
Width W6 (imperial)	1.5 "
Width W6 (metric)	38.1 mm
Height H (imperial)	2.06 "
Height H (metric)	52.3 mm
Mounting Hole Centers (imperial)	4.0 "
Mounting Hole Centers (metric)	101.6 mm

#### Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	120 ft
Package Quantity	36.6 m
Carton Quantity	120

#### **Material and Specifications**

Material Shortcut	PVC
CSA Certified	Yes
Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)
ROHS Conformity	Yes
Certification / Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2014