# HellermannTyton

## 181-44024

Article Number: 181-44024

Slotted Wall Wiring Duct, Intrinsic Blue, 4" X 4", Non-Adhesive, PVC, Blue, 120ft/Carton

# HellermannTyton

RoHS

#### Base Data

Local Order Number	181-44024
Туре	SL4X4
Color	Blue (BU)
Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening design in the finger of the duct helps keep wires in place.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li> </ul>
Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".
Short Description	Slotted Wall Wiring Duct, Intrinsic Blue, 4" X4", Non-Adhesive, PVC, Blue, 120ft/Carton

#### **Product Dimensions**

Length L (imperial)	6.0 ft
Length L (metric)	1.83 m
Width W (imperial)	4.0 "
Width W (metric)	101.6 mm
Width W2 (imperial)	4.0 "
Width W2 (metric)	10.6 mm
Width W3 (imperial)	0.4 "
Width W3 (metric)	10.16 mm
Width W4 (imperial)	1.0 "
Width W4 (metric)	25.4 mm
Width W5 (imperial)	3.6 "
Width W5 (metric)	91.4 mm
Width W6 (imperial)	1.5 "
Width W6 (metric)	38.1 mm
Height H (imperial)	4.0 "
Height H (metric)	101.6 mm
Mounting Hole Centers (imperial)	4.0 "
Mounting Hole Centers (metric)	101.6 mm

#### Logistics and Packaging

Quantity per carton Package Quantity (imperial) 120 ft

Package Quantity 36.6 m

Carton Quantity 120

## Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
CSA Certified	Yes
Flammability	self-extinguishing
Operating Temperature	+122 °F (+50 °C)
ROHS Conformity	Yes
Certification / Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2014