

181-75750

Article Number: 181-75750

Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, Grey, 30ft/Box

HellermannTyton



## Base Data

Local Order Number 181-75750

Type SD.75X75

Color Gray (GY)

**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, Grey, 30ft/Box

## Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 1.5 "

Width W (metric) 38.1 mm

Width W2 (imperial) 1.5 "

Width W2 (metric) 38.1 mm

Height H (imperial) 1.05 "

Height H (metric) 26.7 mm

Mounting Hole Centers (imperial) 4.0 "

Mounting Hole Centers (metric) 101.6 mm

## Logistics and Packaging

Quantity per box

Package Quantity (imperial) 30

Package Quantity 30

Carton Quantity 120

## Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

CSA Certified Yes

Flammability self-extinguishing

**Operating Temperature** +122 °F (+50 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL  
CSA

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes

**UL Recognized (US)** Yes