HellermannTyton

184-11004



Article Number: 184-11004

High Density Slotted Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Gray, 120ft/Carton

RoHS

Base Data

Local Order Number 184-11004

Type SLHD1X1

Color Gray (GY)

Features and Benefits • Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

· Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier

installation.

• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to

accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to

standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily

accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" X1", Non-Adhesive, PVC, Gray, 120ft/Carton

Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 1.0 "

Width W (metric) 25.4 mm

Width W2 (imperial) 1.0 "

Width W2 (metric) 25.4 mm

Width W3 (imperial) 0.16 "

Width W3 (metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 0.75 "

Width W5 (metric) 19.1 mm

Height H (imperial)

Height H (metric) 26.7 mm

Mounting Hole Centers (imperial) 2.0 "

Mounting Hole Centers (metric) 50.8 mm

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 120 ft

Package Quantity

Carton Quantity 120

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

CSA Certified Yes

Flammability self-extinguishing

Operating Temperature +122 °F (+50 °C)

ROHS Conformity Yes

Certification / Specification CSA

1 11

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes