



184-11009



Article Number: 184-11009

High Density Slotted Wall Wiring Duct, 1" X 1.5", Adhesive, PVC, White, 120ft/Carton

 RoHS

Base Data

| | |
|-----------------------|---|
| Local Order Number | 184-11009 |
| Type | SLHDA1X1.5 |
| Color | White (WH) |
| Features and Benefits | <ul style="list-style-type: none">• Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.• Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation. |
| Product Description | Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| Short Description | High Density Slotted Wall Wiring Duct, 1" X 1.5", Adhesive, PVC, White, 120ft/Carton |

Product Dimensions

| | |
|---------------------|---------|
| Length L (imperial) | 6.0 ft |
| Length L (metric) | 1.83 m |
| Width W (imperial) | 1.02 " |
| Width W (metric) | 25.9 mm |
| Width W2 (imperial) | 1.0 " |
| Width W2 (metric) | 25.4 mm |
| Width W3 (imperial) | 0.16 " |
| Width W3 (metric) | 4.1 mm |
| Width W4 (imperial) | 0.4 " |
| Width W4 (metric) | 10.2 mm |
| Width W5 (imperial) | 1.19 " |
| Width W5 (metric) | 30.2 mm |
| Height H (imperial) | 1.56 " |
| Height H (metric) | 34.6 mm |

Logistics and Packaging

| | |
|-----------------------------|--------|
| Quantity per | carton |
| Package Quantity (imperial) | 120 ft |
| Package Quantity | 120 |
| Carton Quantity | 120 |

Material and Specifications

| | |
|--------------------------------------|-------------------------|
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| CSA Certified | Yes |
| Flammability | self-extinguishing |
| Operating Temperature | +122 °F (+50 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | CSA UL |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | No |
| UL Recognized (US) | Yes |