



184-15102



Article Number: 184-15102

High Density Slotted Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, White, 120ft/Carton

 RoHS

Base Data

|                       |   |
|-----------------------|---|
| Local Order Number    | 184-15102   |
| Type                  | SLHD1.5X1   |
| Color                 | White (WH)  |
| Features and Benefits | <ul style="list-style-type: none"><li>• Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li><li>• Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li><li>• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.</li></ul> |
| Product Description   | Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.  |
| Short Description     | High Density Slotted Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, White, 120ft/Carton  |

Product Dimensions

|                                  |         |
|----------------------------------|---------|
| Length L (imperial)              | 6.0 ft  |
| Length L (metric)                | 1.83 m  |
| Width W (imperial)               | 1.5 "   |
| Width W (metric)                 | 38.1 mm |
| Width W2 (imperial)              | 1.5 "   |
| Width W2 (metric)                | 38.1 mm |
| Width W3 (imperial)              | 0.16 "  |
| Width W3 (metric)                | 4.1 mm  |
| Width W4 (imperial)              | 0.4 "   |
| Width W4 (metric)                | 10.2 mm |
| Width W5 (imperial)              | 0.75 "  |
| Width W5 (metric)                | 19.1 mm |
| Height H (imperial)              | 1.05 "  |
| Height H (metric)                | 26.7 mm |
| Mounting Hole Centers (imperial) | 2.0 "   |
| Mounting Hole Centers (metric)   | 50.8 mm |

Logistics and Packaging

|                             |        |
|-----------------------------|--------|
| Quantity per                | carton |
| Package Quantity (imperial) | 120 ft |
| Package Quantity            | 120    |
| Carton Quantity             | 120    |

Material and Specifications

---

|                               |                         |
|-------------------------------|-------------------------|
| Material                      | Polyvinylchloride (PVC) |
| Material Shortcut             | PVC                     |
| CSA Certified                 | Yes                     |
| Flammability                  | self-extinguishing      |
| Operating Temperature         | +122 °F (+50 °C)        |
| ROHS Conformity               | Yes                     |
| Certification / Specification | CSA<br>UL               |
| UL Listed (US and Canada)     | No                      |
| UL Recognized (US and Canada) | No                      |
| UL Recognized (US)            | Yes                     |