

1FRP9C



Article Number: 161-05001

Spiralwrap, 0.125" Diameter, PE-FR, Natural, 100ft/reel

 RoHS

Base Data

|                       |                                                                                                                                                                                                                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number    | 1FRP9C                                                                                                                                                                                                                                                                               |
| Type                  | 1FRP                                                                                                                                                                                                                                                                                 |
| Color                 | Natural (NA)                                                                                                                                                                                                                                                                         |
| Features and Benefits | <ul style="list-style-type: none"><li>• Sheathing allows flexible routing and lead-out of cables</li><li>• The inner edges are beveled preventing damage to cables</li><li>• Sheathing is reusable and resistant to most chemicals</li><li>• Spiralwrap is U.L. Recognized</li></ul> |
| Product Description   | HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.                                                                                                             |
| Variant               | Spiral Binding                                                                                                                                                                                                                                                                       |
| Short Description     | Spiralwrap, 0.125" Diameter, PE-FR, Natural, 100ft/reel                                                                                                                                                                                                                              |

Product Dimensions

|                                |          |
|--------------------------------|----------|
| Length L (imperial)            | 100.0 ft |
| Length L (metric)              | 30.48 m  |
| Bundle Diameter min (imperial) | 0.0625 " |
| Bundle Diameter min (metric)   | 1.6 mm   |
| Bundle Diameter max (imperial) | 0.5 "    |
| Bundle Diameter max (metric)   | 12.7 mm  |
| Diameter D (imperial)          | 0.125 "  |
| Diameter D (metric)            | 3.18 mm  |

|                              |         |
|------------------------------|---------|
| Wall Thickness WT (imperial) | 0.03 "  |
| Wall Thickness WT (metric)   | 0.81 mm |
| Pitch (imperial)             | 0.187 " |
| Pitch (metric)               | 4.75 mm |

Logistics and Packaging

|                             |         |
|-----------------------------|---------|
| Quantity per                | reel    |
| Package Quantity (imperial) | 100 ft  |
| Package Quantity            | 30.48 m |
| Carton Quantity             | 100     |

Material and Specifications

|                   |                                       |
|-------------------|---------------------------------------|
| Material          | Polyethylene, flame-retardant (PE-FR) |
| Material Shortcut | PEFR                                  |
| Flammability      | UL94 V0                               |

**Operating Temperature** -4°F to +176°F (-20°C to +80°C)

**ROHS Conformity** Yes

**UL Recognized (US)** Yes