

318-60155



Article Number: 318-60155

Heat Shrink Tubing, 4FT-Stick, Adhesive Lined, 3:1, 3/4", 19.0/6.0 dia., Polyolefin, Black, 15/pkg

 RoHS

Base Data

Local Order Number	318-60155
Type	TAN33-ST-19/6 BK
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Adhesive lining provides an excellent seal against moisture and humidity.</li><li>• 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters, while thin exterior wall is very flexible and provides superior insulation.</li><li>• Meets UL224 VW-1 specifications making it ideal high heat applications (excludes clear tubing).</li><li>• Polyolefin material provides mechanical strength with good resistance to solvents, oils and fuels.</li></ul>
Product Description	TAN33 is a flexible, thin wall adhesive lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity. 4-foot sticks are individually labeled for retail.
Printable (Yes/No)	No
Shrink Ratio	3:1
Variant	Thin-Wall
Short Description	Heat Shrink Tubing, 4FT-Stick, Adhesive Lined, 3:1, 3/4", 19.0/6.0 dia., Polyolefin, Black, 15/pkg
With inner glue (Yes/No) ETIM	Yes

Product Dimensions

Length L (imperial)	4.0 ft
Length L (metric)	1.22 m
Wall Thickness WT (imperial)	0.085 "
Wall Thickness WT (metric)	2.15 mm
Recovered Diameter D (metric)	6.0 mm
Recovered Diameter D (imperial)	0.236 "
Supplied Diameter D (imperial)	0.748 "
Supplied Diameter D (metric)	19.0 mm

Logistics and Packaging

Quantity per	pack
Package Quantity (imperial)	15
Package Quantity	15

Material and Specifications

Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X

<b>Elongation at break</b>	400%
<b>Halogenfree</b>	No
<b>Shrink Temperature</b>	+212 °F (+100 °C)
<b>Operating Temperature</b>	-67 °F to +257 °F (-55 °C to +125 °C)
<b>ROHS Conformity</b>	Yes
<b>Tensile Strength (MPa)</b>	12 MPa
<b>UL Recognized (US)</b>	Yes
<b>Volume Resistance (Ohm cm)</b>	10 <sup>11</sup> Ω cm