

333-41511

Article Number: 333-41511

Heat Shrink Tubing, 4FT-Stick, 3:1, 3/8", 9.5/3.0 dia., Polyolefin, Black, 15/pkg

HellermannTyton



Base Data

Local Order Number 333-41511

Type TFN31-ST-9/3 BK

Color Black (BK)

Features and Benefits

- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
- Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
- Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
- Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

Product Description TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

Shrink Ratio 3:1

Variant Thin-Wall

Short Description Heat Shrink Tubing, 4FT-Stick, 3:1, 3/8", 9.5/3.0 dia., Polyolefin, Black, 15/pkg

With inner glue (Yes/No) ETIM No

Product Dimensions

Length L (metric) 1.22 m

Wall Thickness WT (imperial) 0.029 "

Wall Thickness WT (metric) .75 mm

Recovered Diameter D (metric) 3.0 mm

Recovered Diameter D (imperial) 0.188 "

Supplied Diameter D (imperial) 0.375 "

Supplied Diameter D (metric) 9.5 mm

Logistics and Packaging

Quantity per lengths

Package Quantity (imperial) 15

Material and Specifications

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Dielectric Strength (metric) 20 kV/mm

Elongation at break 600%

Flammability UL224 VW-1

Halogenfree	No
Shrink Temperature	+212 °F (+100 °C)
Operating Temperature	-67 °F to +275 °F (-55 °C to +135 °C)
ROHS Conformity	Yes
Certification / Specification	CSA UL224 125 °C 600V VW-1
Tensile Strength (MPa)	14 MPa
UL Recognized (US)	Yes
Volume Resistance (Ohm cm)	10 ¹¹ Ω cm