HellermannTyton

380-03001



Article Number: 380-03001

Heat Shrink Tubing, 3:1 Basic Kit, assorted dia. & lengths, Polyolefin Black, 220 pcs/pkg

RoHS

Base Data

Local Order Number 380-03001

Type ShrinKit 321 Basic

Color Black (BK)

Features and Benefits • The basic kit contains 220 pieces of black polyolefin heat shrink tubing in assorted diameter sizes and lengths.

• The 3 to 1 shrink ratio covers a wide range of components, sizes and shapes.

· Material is self-extinguishing, for use in applications in which non-flammable materials are required.

Product Description Heat shrink kits are a convenient solution for "on-the-job" projects. This 3 to 1 shrink ratio tubing features a flexible,

thin wall to cover a wide range of components, sizes and shapes. The polyolefin material has a higher operating temperature range than general-use heat shrink tubing. The basic kit contains an assortment of black color tubing in

variety of diameter sizes and lengths.

Printable (Yes/No) No

Shrink Ratio 3:1

Short Description Heat Shrink Tubing, 3:1 Basic Kit, assorted dia. & lengths, Polyolefin Black, 220 pcs/pkg

With inner glue (Yes/No) ETIM No

Product Dimensions

Logistics and Packaging

Quantity per kit

Package Quantity 1

Carton Quantity 22 Pieces

Weight (Metric) 0.16 kg

Material and Specifications

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Dielectric Strength (metric) 20 kV/mm according to ASTM D 2671

Elongation at break 600%

Flammability self-extinguishing

Shrink Temperature +194 °F (+90 °C)

Operating Temperature -67 °F to +275 °F (-55 °C to +135 °C)

ROHS Conformity Yes

Certification / Specification SAE - AMS - DTL-23053/5 Class 1

Tensile Strength (MPa) 14 MPa

