HellermannTyton

380-03005



Article Number: 380-03005

Heat Shrink Tubing, 3:1 Assorted Universal Kit, assorted dia., color & lengths, Polyolefin, Assorted Colors, 177 pcs/pkg

RoHS

Base Data

Local Order Number 380-03005

Type ShrinKit 321 Universal Basic

Color Various (DIV)

Features and Benefits • The universal kit contains 177 pieces of tubing in assorted colors, diameter sizes and lengths.

• The 3 to 1 shrink ratio covers a wide range of components, sizes and shapes.

• Material is self-extinguishing, for use in applications in which non-flammable materials are required (excludes

clear).

Product Description Heat shrink kits are a convenient solution for "on-the-job" projects. This 3 to 1 shrink ratio tubing features a flexible,

thin wall to cover a wide range of components, sizes and shapes. The polyolefin material has a higher operating temperature range than general-use heat shrink tubing. The universal kit contains an assortment of tubing in different

diameter sizes, colors and lengths.

Printable (Yes/No) No

Shrink Ratio 3:

Short Description Heat Shrink Tubing, 3:1 Assorted Universal Kit, assorted dia., color & lengths, Polyolefin, Assorted Colors, 177

pcs/pkg

With inner glue (Yes/No) ETIM No

Product Dimensions

Logistics and Packaging

Quantity per kit

Package Quantity 1

Weight (Metric) 0.16 kg

Material and Specifications

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Dielectric Strength (metric) 20 kV/mm according to ASTM D 2671

Elongation at break 600%

Flammability self-extinguishing

Shrink Temperature +194 °F (+90 °C)

Operating Temperature -67 °F to +275 °F (-55 °C to +135 °C)

ROHS Conformity Yes

Certification / Specification SAE - AMS - DTL-23053/5 Class 1

Tensile Strength (MPa) 14 MPa