

3P9C



Article Number: 161-05056

Spiralwrap, 0.5" Diameter, PTFE, Natural, 100ft/reel

 RoHS

Base Data

Local Order Number	3P9C
Type	3P
Color	Natural (NA)
Features and Benefits	• Sheathing allows flexible routing and lead-out of cables • The inner edges are beveled preventing damage to cables • Sheathing is reusable and resistant to most chemicals • Spiralwrap is U.L. Recognized
Product Description	HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.
Variant	Spiral Binding
Short Description	Spiralwrap, 0.5" Diameter, PTFE, Natural, 100ft/reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Bundle Diameter min (imperial)	0.375 "
Bundle Diameter min (metric)	9.52 mm
Bundle Diameter max (imperial)	3.0 "
Bundle Diameter max (metric)	76.2 mm
Diameter D (imperial)	0.5 "
Diameter D (metric)	12.7 mm
Wall Thickness WT (imperial)	0.03 "
Wall Thickness WT (metric)	0.76 mm
Pitch (imperial)	0.5 "
Pitch (metric)	12.7 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	30.48 m
Carton Quantity	100
Reel Length (metric)	3 m
Reel Length (imperial)	10.0 ft

Material and Specifications

Material	Polytetrafluoroethylene -Teflon (PTFE)
----------	--

Material Shortcut	PTFE
Flammability	non flammable
Operating Temperature	-449°F to +500°F (-267°C to +260°C)
ROHS Conformity	Yes
UL Recognized (US)	Yes