

Article Number: 590-05141

Rite-On Self-Laminating Label Refill, .75" X .375" X 1.25", Vinyl, White, 200/RL



Base Data

|                                     |  |
|-------------------------------------|--|
| Local Order Number                  | 514REF   |
| Type                                | 514REF   |
| Color                               | White (WH)   |
| Features and Benefits               | <ul style="list-style-type: none"><li>• Compact to easily fit in pants or shirt pockets. _x000D_</li><li>• Dispenser can be reloaded over and over, making it cost effective to use. _x000D_</li><li>• Dispenser edge allows easy removal of label liner. _x000D_</li><li>• Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.</li></ul> |
| Color Marking Field                 | White (WH)   |
| Product Description                 | HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.                               |
| Fixation Method (FF)                | Pasting / Stick  |
| Mounting method Identification ETIM | Pasting / Stick  |
| Self adhesive (Yes/No)              | Yes  |
| Variant                             | Roller form  |
| Short Description                   | Rite-On Self-Laminating Label Refill, .75" X .375" X 1.25", Vinyl, White, 200/RL   |
| With label space ETIM               | Yes  |

Product Dimensions

|                                  |                |
|----------------------------------|----------------|
| Length L (imperial)              | 0.375 "        |
| Length L (metric)                | 9.52 mm        |
| Core diameter from / to          | 3.89 - 6.68 mm |
| Width W (imperial)               | 0.75 "         |
| Width W (metric)                 | 19.05 mm       |
| Height H (imperial)              | 0.375 "        |
| Height H (metric)                | 9.52 mm        |
| Height H2 (imperial)             | 1.25 "         |
| Height H2 (metric)               | 31.75 mm       |
| Bundle Diameter min (imperial)   | 0.15 "         |
| Bundle Diameter min (metric)     | 3.89 mm        |
| Bundle Diameter max (imperial)   | 0.263 "        |
| Bundle Diameter max (metric)     | 6.68 mm        |
| Outside Diameter min. (imperial) | 0.153 "        |
| Outside Diameter min. (metric)   | 3.89 mm        |
| Outside Diameter max. (imperial) | 0.263 "        |

|                                       |             |
|---------------------------------------|-------------|
| <b>Outside Diameter max. (metric)</b> | 6.68 mm     |
| <b>Wire Size Range (AWG)</b>          | 14 to 8 AWG |

## Logistics and Packaging

|                                    |          |
|------------------------------------|----------|
| <b>Quantity per</b>                | pack     |
| <b>Package Quantity (imperial)</b> | 200      |
| <b>Package Quantity</b>            | 200      |
| <b>Carton Quantity</b>             | 1        |
| <b>Weight (Metric)</b>             | 0.075 kg |

## Material and Specifications

|                                       |   |
|---------------------------------------|---|
| <b>Material</b>                       | Type 100, self laminating Vinyl, white (WH) |
| <b>Material Shortcut</b>              | 100   |
| <b>Adhesive</b>                       | Acrylic                                     |
| <b>Shortcut Adhesive</b>              | Acryl                                       |
| <b>Adhesive Operating Temperature</b> | -51 °F to +200 °F (-46 °C to +93 °C)        |
| <b>Operating Temperature</b>          | -51 °F to +200 °F (-46 °C to +93 °C)        |
| <b>ROHS Conformity</b>                | Yes   |