


553-50010

Article Number: 553-50010

Heat Shrink Labels, .187" Single Sided, Polyolefin, White, 1000/BX



## Base Data

Local Order Number 553-50010

Type HST4.8-1.6WH

Color White (WH)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Printable (Yes/No) Yes

Variant Thin-Wall

Short Description Heat Shrink Labels, .187" Single Sided, Polyolefin, White, 1000/BX

With inner glue (Yes/No) ETIM No

## Product Dimensions

Length L (imperial) 1.9 "

Length L (metric) 48.3 mm

Height H (imperial) 0.31 "

Height H (metric) 7.9 mm

Diameter max. (imperial) 0.187 "

Outside Diameter max. (imperial) 0.187 "

Wall Thickness WT (imperial) 0.028 "

Wall Thickness WT (metric) 0.65 mm

Print Method Thermal Transfer

Recovered Diameter D (metric) 1.6 mm

Recovered Diameter D (imperial) 0.063 "

Supplied Diameter D (imperial) 0.177 "

Supplied Diameter D (metric) 4.8 mm

Thickness T (Metric) 3.0 µm

Width of Liner WL (imperial) 3.0 "

Width of Liner WL (metric) 76.2 mm

## Logistics and Packaging

Quantity per roll

**Package Quantity (imperial)** 1000  
**Package Quantity** 1000  
**Markers per row** 1  
**Weight (imperial)** 1.39 lbs  
**Weight (Metric)** 0.635 kg

## Material and Specifications

---

**Material** Polyolefin, cross-linked (PO-X)  
**Material Shortcut** PO-X  
**US MILSPEC** SAE-AS81531  
MIL-STD-202G Method 215K  
AMS-DTL-23053/5 Class 1 and 3  
**Abrasion Resistance** Good  
**Dielectric Strength (metric)** 19.7 kV min.  
**Flammability** UL224 VW-1  
**Shrink Temperature** +194 °F (+90 °C)  
**Operating Temperature** -67 °F to +275 °F (-55 °C to +135 °C)  
**Recommended Ribbon Type** TTDTHOUT  
TTRC+  
**ROHS Conformity** Yes  
**Certification / Specification** SAE-AS81531  
AMS-DTL-23053/5 Class 1 and 3  
MIL-STD-202G Method 215K  
UL224 125 °C 600V VW-1