

553-50038

Article Number: 553-50038

Heat Shrink Labels, 1.0" Single Sided, Polyolefin, Black, 250/BX



Base Data

Local Order Number 553-50038

Type HST24-8BK

Color Black (BK)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
 - Smooth surface for clean and legible printing.
 - Supplied on a ladder style carrier so that markers can be kitted after printing.
 - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

Product Description HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Printable (Yes/No) Yes

Variant Thin-Wall

Short Description Heat Shrink Labels, 1.0" Single Sided, Polyolefin, Black, 250/BX

With inner glue (Yes/No) ETIM No

Product Dimensions

Length L (imperial) 1.9 "

Length L (metric) 48.3 mm

Height H (imperial) 1.69 "

Height H (metric) 42.93 mm

Diameter max. (imperial) 1.0 "

Outside Diameter max. (imperial) 1.0 "

Outside Diameter max. (metric) 25.4 mm

Wall Thickness WT (imperial) 0.024 "

Wall Thickness WT (metric) 1.20 mm

Print Method Thermal Transfer

Recovered Diameter D (metric) 8.0 mm

Recovered Diameter D (imperial) 0.33 "

Supplied Diameter D (imperial) 1.57 "

Supplied Diameter D (metric) 24.0 mm

Thickness T (Metric) 3.0 µm

Width of Liner WL (imperial) 3.0 "

Width of Liner WL (metric) 76.2 mm

Logistics and Packaging

Quantity per roll
Package Quantity 250
Markers per row 1
Weight (imperial) 1.48 lbs
Weight (Metric) 0.68 kg

Material and Specifications

Material Polyolefin, cross-linked (PO-X)
Material Shortcut PO-X
US MILSPEC AMS-DTL-23053/5 Class 1 and 3
SAE-AS81531
MIL-STD-202G Method 215K
Abrasion Resistance Good
Dielectric Strength (metric) 19.7 kV min.
Flammability UL224 VW-1
Shrink Temperature +194 °F (+90 °C)
Operating Temperature -67 °F to +275 °F (-55 °C to +135 °C)
Recommended Ribbon Type TTDTHOUT
TTRC+
ROHS Conformity Yes
Certification / Specification SAE-AS81531
UL224 125 °C 600V VW-1
AMS-DTL-23053/5 Class 1 and 3
MIL-STD-202G Method 215K