# HellermannTyton

## 556-00165

Article Number: 556-00165

Thermal Transfer Ribbon, SwiftMark, 2.0" X 984', 1" Core, 100 Resin, Black, 1/EA

HellermannTyton

RoHS

### Base Data

Local Order Number	556-00165
Туре	SM100OUT
Color	Black (BK)
Features and Benefits	<ul> <li>Ribbons are resin based for the best print durability.</li> <li>Ribbons are available to fit all HellermannTyton printers for easy resupply.</li> <li>Ribbons are available in colors for maximizing design printing capabilities.</li> <li>Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.</li> </ul>
Product Description	HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.
Variant	Coloured ribbon
Short Description	Thermal Transfer Ribbon, SwiftMark, 2.0" X 984', 1" Core, 100 Resin, Black, 1/EA

#### **Product Dimensions**

Length L (imperial)	984.0 ft
Length L (metric)	300.0 m
Width W (imperial)	2.0 "
Width W (metric)	50.8 mm
Print Method	Thermal Transfer
Recommended Material	100B

#### Logistics and Packaging

Quantity per	EA
Package Quantity (imperial)	1
Package Quantity	1
Carton Quantity	24
Reel Diameter (imperial)	2.5 "
Reel Diameter (metric)	63.5 cm
Reel Length (imperial)	984.0 ft
Reel Length (metric)	300 m
Reel Width (imperial)	2.0 "
Reel Width (metric)	50.8 mm
Weight (imperial)	1.0 lbs
Weight (Metric)	0.45 kg

MaterialPolyester FilmMaterial ShortcutPETOperating Temperature+40 °F to +300 °F (+4 °C to +82 °C)ROHS ConformityYes

© HellermannTyton 2014