

Article Number: 558-00045

SwiftMark Self-Laminating Label, .5" X .5" X 1.437", Vinyl, White, 2500/RL



Base Data

Local Order Number 558-00045

Type TAG38-76W127SM

Color White (WH)

- Features and Benefits**
- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
 - Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
 - Labels are UL recognized for indoor and outdoor use to expand application options.
 - HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

Product Description HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, .5" X .5" X 1.437", Vinyl, White, 2500/RL

With label space ETIM Yes

Product Dimensions

Core diameter from / to 3.5 - 7.6 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Height H (imperial) 0.5 "

Height H (metric) 12.7 mm

Height H2 (imperial) 1.437 "

Height H2 (metric) 36.49 mm

Bundle Diameter min (imperial) 0.137 "

Bundle Diameter min (metric) 3.5 mm

Bundle Diameter max (imperial) 0.29 "

Bundle Diameter max (metric) 7.6 mm

Outside Diameter min. (imperial) 0.137 "

Outside Diameter min. (metric) 3.5 mm

| | |
|---|------------------|
| Outside Diameter max. (imperial) | 0.299 " |
| Outside Diameter max. (metric) | 7.6 mm |
| Horizontal Repeat HR (metric) | 12.7 mm |
| Horizontal Repeat HR (imperial) | .5 " |
| Print Method | Thermal Transfer |
| Thickness T (Metric) | 25 µm |
| Thickness of Foil (TF) | 35 µm |
| Vertical Repeat VR (imperial) | 1.687 " |
| Vertical Repeat VR (metric) | 42.84 mm |
| Width of Liner WL (imperial) | 0.9 " |
| Width of Liner WL (metric) | 22.86 mm |

Logistics and Packaging

| | |
|------------------------------------|---------|
| Quantity per | roll |
| Package Quantity (imperial) | 2500 |
| Package Quantity | 2500 |
| Carton Quantity | 2500 |
| Labels per Row | 1 |
| Weight (imperial) | 1.3 lbs |
| Weight (Metric) | 0.6 kg |

Material and Specifications

| | |
|---------------------------------------|---|
| Material | Type 100, self laminating Vinyl, white (WH) |
| Material Shortcut | 100B |
| Shortcut Adhesive | Acryl |
| Adhesive | Acrylic |
| Adhesive Operating Temperature | -40 °F to +194 °F (-40 °C to +90 °C) |
| Operating Temperature | -40 °F to +176 °F (-40 °C to +80 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | UL-Recognized |
| UL Recognized (US and Canada) | Yes |