# HellermannTyton

#### 558-00053

Article Number: 558-00053

SwiftMark Self-Laminating Label, 1.5" X .75" X 2.25", Vinyl, White, 1000/RL





#### **Base Data**

Local Order Number 558-00053

TAG61-121W381SM Type

Color White (WH)

Features and Benefits • HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.

· Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over

• Labels are UL recognized for indoor and outdoor use to expand application options.

· HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work

flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

**Product Description** HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer.

Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range

from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, 1.5" X.75" X2.25", Vinyl, White, 1000/RL

With label space ETIM Yes

#### **Product Dimensions**

Core diameter from / to 5.5 - 12.1 mm

Width W (imperial) 1.5"

Width W (metric) 38.1 mm

Height H (imperial) 0.75 "

Height H (metric) 19.05 mm

Height H2 (imperial) 2.25 "

Height H2 (metric) 57.1 mm

Bundle Diameter min (imperial) 0.21 "

Bundle Diameter min (metric) 5.5 mm

Bundle Diameter max (imperial) 0.47 "

Bundle Diameter max (metric) 12.1 mm

Outside Diameter min. (imperial) 0.216 "

Outside Diameter min. (metric) 5.5 mm

Outside Diameter max. (imperial) 0.476 "

Outside Diameter max. (metric) 12.1 mm

Horizontal Repeat HR (metric) 38.1 mm

Horizontal Repeat HR (imperial) 1.5 "

Print Method Thermal Transfer

Thickness T (Metric) 25 µm

Thickness of Foil (TF) 35 µm

Vertical Repeat VR (imperial) 2.62 "

Vertical Repeat VR (metric) 66.67 mm

Width of Liner WL (imperial) 1.625 "

Width of Liner WL (metric) 41.27 mm

## **Logistics and Packaging**

Quantity per roll

Package Quantity (imperial) 1000

Package Quantity 1000

Carton Quantity 1000

Labels per Row 1

Weight (imperial) 1.68 lbs

Weight (Metric) 0.76 kg

## **Material and Specifications**

Material Type 100, self laminating Vinyl, white (WH)

Material Shortcut 100B

Shortcut Adhesive Acryl

Adhesive Acrylic

Adhesive Operating Temperature -40 °F to +194 °F (-40 °C to +90 °C)

Operating Temperature -40 °F to +176 °F (-40 °C to +80 °C)

ROHS Conformity Yes

Certification / Specification UL-Recognized