

Article Number: 558-00056

SwiftMark Self-Laminating Label, 1.5" X 1.0" X 3.0", Vinyl, White, 1000/RL



## Base Data

Local Order Number 558-00056

Type TAG85-100W381SM

Color White (WH)

**Features and Benefits**

- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

**Product Description** HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, 1.5" X 1.0" X 3.0", Vinyl, White, 1000/RL

With label space ETIM Yes

## Product Dimensions

Core diameter from / to 10.1 - 20.2 mm

Width W (imperial) 1.5 "

Width W (metric) 38.1 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Height H2 (imperial) 3.0 "

Height H2 (metric) 76.2 mm

Bundle Diameter min (imperial) 0.39 "

Bundle Diameter min (metric) 10.1 mm

Bundle Diameter max (imperial) 0.7 "

Bundle Diameter max (metric) 17.70 mm

Outside Diameter min. (imperial) 0.79 "

Outside Diameter min. (metric) 10.1 mm

|   |                  |
|---|------------------|
| <b>Outside Diameter max. (imperial)</b> | 0.39 "           |
| <b>Outside Diameter max. (metric)</b>   | 20.2 mm          |
| <b>Horizontal Repeat HR (metric)</b>    | 38.1 mm          |
| <b>Horizontal Repeat HR (imperial)</b>  | 1.5 "            |
| <b>Print Method</b>                     | Thermal Transfer |
| <b>Thickness T (Metric)</b>             | 35 µm            |
| <b>Thickness of Foil (TF)</b>           | 35 µm            |
| <b>Vertical Repeat VR (imperial)</b>    | 3.25 "           |
| <b>Vertical Repeat VR (metric)</b>      | 82.55 mm         |
| <b>Width of Liner WL (imperial)</b>     | 1.625 "          |
| <b>Width of Liner WL (metric)</b>       | 41.27 mm         |

## Logistics and Packaging

---

|                                    |         |
|------------------------------------|---------|
| <b>Quantity per</b>                | roll    |
| <b>Package Quantity (imperial)</b> | 1000    |
| <b>Package Quantity</b>            | 1000    |
| <b>Carton Quantity</b>             | 1000    |
| <b>Labels per Row</b>              | 1       |
| <b>Weight (imperial)</b>           | 2.08    |
| <b>Weight (Metric)</b>             | 0.94 kg |

## Material and Specifications

---

|                                       |   |
|---------------------------------------|---|
| <b>Material</b>                       | Type 100, self laminating Vinyl, white (WH) |
| <b>Material Shortcut</b>              | 100B  |
| <b>Shortcut Adhesive</b>              | Acryl                                       |
| <b>Adhesive</b>                       | Acrylic                                     |
| <b>Adhesive Operating Temperature</b> | -40 °F to +194 °F (-40 °C to +90 °C)        |
| <b>Operating Temperature</b>          | -40 °F to +176 °F (-40 °C to +80 °C)        |
| <b>ROHS Conformity</b>                | Yes   |
| <b>Certification / Specification</b>  | UL-Recognized                               |