# HellermannTyton

### 558-00057

Article Number: 558-00057

SwiftMark Self-Laminating Label, 1.75" X 1.0" X 3.0", Vinyl, White, 1000/RL





#### **Base Data**

Local Order Number 558-00057

TAG85-100W444SM Type

Color White (WH)

Features and Benefits • HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.

· Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over

Labels are UL recognized for indoor and outdoor use to expand application options.

· HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work

flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

Product Description

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range

from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, 1.75" X 1.0" X 3.0", Vinyl, White, 1000/RL

With label space ETIM Yes

# **Product Dimensions**

Core diameter from / to 10.1 - 20.2 mm

Width W (imperial) 1.75 "

Width W (metric) 44.45 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Height H2 (imperial) 3.0 "

Height H2 (metric) 76.2 mm

Bundle Diameter min (imperial) 0.39 "

Bundle Diameter min (metric) 10.1 mm

Bundle Diameter max (imperial) 0.7 "

Bundle Diameter max (metric) 17.70 mm

Outside Diameter min. (imperial) 0.79 "

Outside Diameter min. (metric) 10.1 mm

Outside Diameter max. (imperial) 0.39 "

Outside Diameter max. (metric) 20.2 mm

Horizontal Repeat HR (metric) 44.45 mm

Horizontal Repeat HR (imperial) 1.75 "

Print Method Thermal Transfer

Thickness T (Metric) 35 µm

Thickness of Foil (TF) 35 µm

Vertical Repeat VR (imperial) 3.25 "

Vertical Repeat VR (metric) 82.55 mm

Width of Liner WL (imperial) 1.875 "

Width of Liner WL (metric) 47.62 mm

# **Logistics and Packaging**

Quantity per roll

Package Quantity (imperial) 1000

Package Quantity 1000

Carton Quantity 1000

Labels per Row 1

Weight (imperial) 2.42

Weight (Metric) 1.1 kg

# **Material and Specifications**

Material Type 100, self laminating Vinyl, white (WH)

Material Shortcut 100B

Shortcut Adhesive Acryl

Adhesive Acrylic

Adhesive Operating Temperature -40 °F to +194 °F (-40 °C to +90 °C)

Operating Temperature -40 °F to +176 °F (-40 °C to +80 °C)

ROHS Conformity Yes

Certification / Specification UL-Recognized