

Article Number: 558-00069

SwiftMark Self-Laminating Label, 1.0" X .35" X 1.0", Vinyl, White, 5000/RL



## Base Data

**Local Order Number** 558-00069

**Type** TAG26-53W254SM

**Color** White (WH)

- Features and Benefits**
- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
  - Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
  - Labels are UL recognized for indoor and outdoor use to expand application options.
  - HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

**Product Description** HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

**Mounting method Identification ETIM** Pasting / Stick

**Variant** Roller form

**Short Description** SwiftMark Self-Laminating Label, 1.0" X .35" X 1.0", Vinyl, White, 5000/RL

**With label space ETIM** Yes

## Product Dimensions

**Core diameter from / to** 2.6 - 5.3 mm

**Width W (imperial)** 1.0 "

**Width W (metric)** 25.4 mm

**Height H (imperial)** 0.35 "

**Height H (metric)** 8.89 mm

**Height H2 (imperial)** 1.0 "

**Height H2 (metric)** 25.4 mm

**Bundle Diameter min (imperial)** 0.1 "

**Bundle Diameter min (metric)** 2.6 mm

**Bundle Diameter max (imperial)** 0.2 "

**Bundle Diameter max (metric)** 5.3 mm

**Outside Diameter min. (imperial)** 0.1 "

**Outside Diameter min. (metric)** 2.6 mm

**Outside Diameter max. (imperial)** 0.2 "

<b>Outside Diameter max. (metric)</b>	5.3 mm
<b>Horizontal Repeat HR (metric)</b>	8.89 mm
<b>Horizontal Repeat HR (imperial)</b>	.35 "
<b>Print Method</b>	Thermal Transfer
<b>Thickness T (Metric)</b>	25 µm
<b>Thickness of Foil (TF)</b>	35 µm
<b>Vertical Repeat VR (imperial)</b>	1.375 "
<b>Vertical Repeat VR (metric)</b>	34.92 mm
<b>Width of Liner WL (imperial)</b>	1.125 "
<b>Width of Liner WL (metric)</b>	28.57 mm

## Logistics and Packaging

---

<b>Quantity per</b>	roll
<b>Package Quantity (imperial)</b>	5000
<b>Package Quantity</b>	5000
<b>Carton Quantity</b>	5000
<b>Labels per Row</b>	1
<b>Weight (imperial)</b>	2.40
<b>Weight (Metric)</b>	1.09 kg

## Material and Specifications

---

<b>Material</b>	Type 100, self laminating Vinyl, white (WH)
<b>Material Shortcut</b>	100B
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40 °F to +194 °F (-40 °C to +90 °C)
<b>Operating Temperature</b>	-40 °F to +176 °F (-40 °C to +80 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL-Recognized