

Article Number: 558-00216

SwiftMark Self-Laminating Label, 2.0" X .5" X 1.0", Vinyl, White, 4500/RL



Base Data

Local Order Number 558-00216

Type TAG20-47W508SM

Color White (WH)

Features and Benefits

- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

Product Description HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, 2.0" X .5" X 1.0", Vinyl, White, 4500/RL

With label space ETIM Yes

Product Dimensions

Core diameter from / to 2.0 - 4.7 mm

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 0.5 "

Height H (metric) 12.7 mm

Height H2 (imperial) 1.0 "

Height H2 (metric) 25.4 mm

Bundle Diameter min (imperial) 0.1 "

Bundle Diameter min (metric) 2.6 mm

Bundle Diameter max (imperial) 0.2 "

Bundle Diameter max (metric) 5.3 mm

Outside Diameter min. (imperial) 0.078 "

Outside Diameter min. (metric) 2.0 mm

Outside Diameter max. (imperial)	0.18 "
Outside Diameter max. (metric)	4.7 mm
Horizontal Repeat HR (metric)	25.4 mm
Horizontal Repeat HR (imperial)	2.0 "
Print Method	Thermal Transfer
Thickness T (Metric)	25 µm
Thickness of Foil (TF)	35 µm
Vertical Repeat VR (imperial)	1.25 "
Vertical Repeat VR (metric)	31.75 mm
Width of Liner WL (imperial)	2.125 "
Width of Liner WL (metric)	53.97 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	4500
Package Quantity	4500
Carton Quantity	4500
Labels per Row	1
Weight (imperial)	4.5
Weight (Metric)	2.04 kg

Material and Specifications

Material	Type 100, self laminating Vinyl, white (WH)
Material Shortcut	100B
Shortcut Adhesive	Acryl
Adhesive	Acrylic
Adhesive Operating Temperature	-40 °F to +194 °F (-40 °C to +90 °C)
Operating Temperature	-51 °F to +200 °F (-46 °C to +93 °C)
ROHS Conformity	Yes