

596-00412



**Article Number:** 596-00412

**Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, White, 500/RL**



## Base Data

**Local Order Number** 596-00412

**Type** NPLH31X31WH22.5

**Color** White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Self adhesive (Yes/No)** Yes

**Short Description** Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, White, 500/RL

## Product Dimensions

**Length L (imperial)** 1.25 "

**Length L (metric)** 31.7 mm

**Width W (imperial)** 1.25 "

**Width W (metric)** 31.7 mm

**Height H (imperial)** 1.25 "

**Height H (metric)** 31.7 mm

**Mounting Hole Diameter D (imperial)** 0.88 "

**Mounting Hole Diameter D (metric)** 22.35 mm

**Horizontal Repeat HR (metric)** 31.7 mm

**Horizontal Repeat HR (imperial)** 1.25 "

**Print Method** Thermal Transfer

**Vertical Repeat VR (imperial)** 1.375 "

**Vertical Repeat VR (metric)** 34.92 mm

**Width of Liner WL (imperial)** 1.5 "

**Width of Liner WL (metric)** 38.1 mm

## Logistics and Packaging

**Quantity per** roll

**Package Quantity (imperial)** 250

**Package Quantity** 250

**Labels per Column** 1  
**Labels per Row** 1  
**Weight (imperial)** 0.5 lbs  
**Weight (Metric)** 0.22 kg

---

## Material and Specifications

---

**Material** Polyester (PET)  
**Material Shortcut** PET  
**Adhesive** Acrylic  
**Shortcut Adhesive** Acryl  
**Adhesive Operating Temperature** -40 °F to +176 °F (-40 °C to +80 °C)  
**Operating Temperature** -40 °F to +176 °F (-40 °C to +80 °C)  
**ROHS Conformity** Yes  
**UL Recognized (US)** Yes