


596-00413



Article Number: 596-00413

Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, Black, 500/RL



Base Data

Local Order Number 596-00413

Type NPLH31X31BK22.5

Color Black (BK)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
 - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
 - Labels are UV and chemical resistant for long life in an industrial environment.
 - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

Product Description Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

Self adhesive (Yes/No) Yes

Short Description Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, Black, 500/RL

Product Dimensions

Length L (imperial) 1.25 "

Length L (metric) 31.7 mm

Width W (imperial) 1.25 "

Width W (metric) 31.7 mm

Height H (imperial) 1.25 "

Height H (metric) 31.7 mm

Mounting Hole Diameter D (imperial) 0.88 "

Mounting Hole Diameter D (metric) 22.35 mm

Horizontal Repeat HR (metric) 31.7 mm

Horizontal Repeat HR (imperial) 1.25 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 1.375 "

Vertical Repeat VR (metric) 34.92 mm

Width of Liner WL (imperial) 1.5 "

Width of Liner WL (metric) 38.1 mm

Logistics and Packaging

Quantity per roll

Package Quantity (imperial) 250

Package Quantity 250

Labels per Column 1
Labels per Row 1
Weight (imperial) 0.5 lbs
Weight (Metric) 0.22 kg

Material and Specifications

Material Polyester (PET)
Material Shortcut PET
Adhesive Acrylic
Shortcut Adhesive Acryl
Adhesive Operating Temperature -40 °F to +176 °F (-40 °C to +80 °C)
Operating Temperature -40 °F to +176 °F (-40 °C to +80 °C)
ROHS Conformity Yes
UL Recognized (US) Yes