# HellermannTyton

# 596-00425

Article Number: 596-00425

Pre-Printed Header Label, CAUTION, 3" X 2", PET, Yellow, 250/RL

CAUTION: SOLAR CIRCUIT

RoHS

### Base Data

| Local Order Number    | 596-00425   |
|-----------------------|---|
| Туре                  | 3X2CAUTION  |
| Color                 | Yellow (YE)   |
| Features and Benefits | <ul> <li>Pre-Printed Signal Word labels come with the header pre-printed in colors so that only one color of ribbon is needed to complete the message panel.</li> <li>Labels are pre-made to the most recent ANSI standards so that code complance is assured.</li> <li>Pre-Printed Signal Panel labels can be printed using standard thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand when needed.</li> </ul> |
| Product Description   | Pre-Printed Signal word labels come pre-printed with the NOTICE, CAUTION, DANGER and SAFETY headers in<br>blue, yellow, red and green as defined by ANSI Z535. The variable body text and be printed using Tagprint Pro<br>labeling software and the HellermannTyton line of thermal transfer printers or any standard thermal transfer printer.<br>Only one color needs to be printed to complete the label, saving time and money.  |
| Short Description     | Pre-Printed Header Label, CAUTION, 3" X 2", PET, Yellow, 250/RL   |

#### **Product Dimensions**

| Length L (imperial) | 2.0 "   |
|---------------------|---------|
| Length L (metric)   | 50.8 mm |
| Width W (imperial)  | 3.0 "   |
| Width W (metric)    | 76.2 mm |
| Height H (imperial) | 2.0 "   |
| Height H (metric)   | 50.8 mm |
|                     |         |

## Logistics and Packaging

| Quantity per                | roll   |
|-----------------------------|--------|
| Package Quantity (imperial) | 250    |
| Package Quantity            | 250    |
| Labels per Column           | 1      |
| Labels per Row              | 1      |
| Weight (imperial)           | 3.2 oz |

#### **Material and Specifications**

| Material                       | Vinyl                                 |
|--------------------------------|---------------------------------------|
| Material Shortcut              | Vinyl                                 |
| Adhesive                       | Acrylic                               |
| Shortcut Adhesive              | Acryl                                 |
| Adhesive Operating Temperature | -40 °F to +302 °F (-40 °C to +150 °C) |

HalogenfreeYesOperating Temperature-40 °F to +302 °F (-40 °C to +150 °C)ROHS ConformityYes

UL Recognized (US) Yes

© HellermannTyton 2014