HellermannTyton

596-00426

Article Number: 596-00426

Pre-Printed Header Label, NOTICE, 3" X 2", PET, Blue, 250/RL

HellermannTyton

RoHS

Base Data

| Local Order Number | 596-00426 |
|-----------------------|---|
| Туре | 3X2NOTICE |
| Color | Blue (BU) |
| Features and Benefits | Pre-Printed Signal Word labels come with the header pre-printed in colors so that only one color of ribbon is needed to complete the message panel. Labels are pre-made to the most recent ANSI standards so that code complance is assured. Pre-Printed Signal Panel labels can be printed using standard thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand when needed. |
| Product Description | Pre-Printed Signal word labels come pre-printed with the NOTICE, CAUTION, DANGER and SAFETY headers in blue, yellow, red and green as defined by ANSI Z535. The variable body text and be printed using Tagprint Pro labeling software and the HellermannTyton line of thermal transfer printers or any standard thermal transfer printer. Only one color needs to be printed to complete the label, saving time and money. |
| Short Description | Pre-Printed Header Label, NOTICE, 3" X2", PET, Blue, 250/RL |

Product Dimensions

| Length L (imperial) | 2.0 " |
|---------------------|---------|
| Length L (metric) | 50.8 mm |
| Width W (imperial) | 3.0 " |
| Width W (metric) | 76.2 mm |
| Height H (imperial) | 2.0 " |
| Height H (metric) | 50.8 mm |

Logistics and Packaging

| Quantity per | roll |
|-----------------------------|--------|
| Package Quantity (imperial) | 250 |
| Package Quantity | 250 |
| Labels per Column | 1 |
| Labels per Row | 1 |
| Weight (imperial) | 3.2 oz |

Material and Specifications

| Material | Vinyl |
|--------------------------------|---------------------------------------|
| Material Shortcut | Vinyl |
| Adhesive | Acrylic |
| Shortcut Adhesive | Acryl |
| Adhesive Operating Temperature | -40 °F to +302 °F (-40 °C to +150 °C) |

HalogenfreeYesOperating Temperature-40 °F to +302 °F (-40 °C to +150 °C)ROHS ConformityYes

UL Recognized (US) Yes

© HellermannTyton 2014