

596-00557

Article Number: 596-00557

Foam Nameplate, 3" X 4" Rectangular Nameplate, PET, Black, 500/RL



Base Data

Local Order Number	596-00557
Type	NPL76X101BK
Color	Black (BK)
Features and Benefits	- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs. - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product. - Labels are UV and chemical resistant for long life in an industrial environment. - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.
Product Description	Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.
Self adhesive (Yes/No)	Yes
Short Description	Foam Nameplate, 3" X 4" Rectangular Nameplate, PET, Black, 500/RL

Product Dimensions

Length L (imperial)	4.0 "
Length L (metric)	101.6 mm
Width W (imperial)	3.0 "
Width W (metric)	76.2 mm
Height H (imperial)	4.0 "
Height H (metric)	101.6 mm
Horizontal Repeat HR (metric)	76 mm
Horizontal Repeat HR (imperial)	3.0 "
Print Method	Thermal Transfer
Vertical Repeat VR (imperial)	4.125 "
Vertical Repeat VR (metric)	104.77 mm
Width of Liner WL (imperial)	3.2 "
Width of Liner WL (metric)	81.28 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	150
Package Quantity	150
Labels per Column	1
Labels per Row	1

Weight (imperial) 0.5 lbs

Weight (Metric) 0.22 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Adhesive Acrylate with base of acrylic foam

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

Operating Temperature -40 °F to +302 °F (-40 °C to +150 °C)

ROHS Conformity Yes