


Article Number: 596-00653

Printable Solar Label, 4" X 2", DC MODULE LABEL, Red, 25/RL



Base Data

Local Order Number	596-00653
Type	DC2011-1
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none">• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.• The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.
Color of Print	White (WH)
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	2" X 4" White text on red background that reads as: "RATED MAX POWER-POINT CURRENT;RATED MAX POWER-POINT CURRENT;MAXIMUM SYSTEM VOLTAGE;MAXIMUM CIRCUIT CURRENT;MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER (IF INSTALLED." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand. Dispensed narrow side first for use in the TT130SMC printer.
Short Description	Printable Solar Label, 4" X 2", DC MODULE LABEL, Red, 25/RL

Product Dimensions

Width W (imperial)	2.0 "
Width W (metric)	50.8 mm
Height H (imperial)	4.0 "
Height H (metric)	101.6 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	50
Package Quantity	50

Material and Specifications

Material	Vinyl
Material Shortcut	Vinyl

Adhesive	Acrylic
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +180 °F (-40 °C to +82 °C)
Halogenfree	Yes
Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Recommended Ribbon Type	TT822OUT
ROHS Conformity	Yes
UL Recognized (US)	Yes