

596-00662

Article Number: 596-00662

Solar Label, Warning - DC Conductors Energized Label, 4.12" X 2.0", Vinyl, Orange/White, 10/pkg



Base Data

Local Order Number 596-00662
 Type WDCCU10
 Color Red (RD)

Features and Benefits

- Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.
- Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.
- Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.
- The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.

Color of Print Black (BK)

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4.12" X2" Black text on Orange/White background that reads as:
 "WARNING - ELECTRICAL SHOCK HAZARD. THE DC CONDUCTORS OF THIS PHOTOVOLTAIC SYSTEM ARE UNGROUNDED AND MAY BE ENERGIZED" - 10 per pkg.

Short Description Solar Label, Warning - DC Conductors Energized Label, 4.12" X2.0", Vinyl, Orange/White, 10/pkg

Product Dimensions

Width W (imperial) 4.12 "
 Width W (metric) 104.6 mm
 Height H (imperial) 2.0 "
 Height H (metric) 50.8 mm

Logistics and Packaging

Quantity per pack
 Package Quantity (imperial) 10
 Package Quantity 10

Material and Specifications

Material Vinyl
 Material Shortcut Vinyl
 Adhesive Acrylic
 Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +174 °F (-40 °C to +79 °C)

Halogenfree Yes

Operating Temperature -40 °F to +174 °F (-40 °C to +79 °C)

ROHS Conformity Yes

UL Recognized (US) Yes