

596-00671



Article Number: 596-00671

Pre-Printed Reflective Solar Label, 6.5" X 1", DO NOT DISCONNECT UNDER LOAD, Red, 10/pkg

RoHS

Base Data

Local Order Number	596-00671
Type	DNDCUL10
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none">• Pre-Printed Reflective Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Reflective Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.• The reflective inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.
Color of Print	White (WH)
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	6.5" X 1" White text on red background that reads as: "DO NOT DISCONNECT UNDER LOAD" in 3/8" tall characters. 10 per pkg.
Short Description	Pre-Printed Reflective Solar Label, 6.5" X 1", DO NOT DISCONNECT UNDER LOAD, Red, 10/pkg

Product Dimensions

Width W (imperial)	6.5 "
Width W (metric)	165.1 mm
Height H (imperial)	1.0 "
Height H (metric)	25.4 mm

Logistics and Packaging

Quantity per	pack
Package Quantity (imperial)	10
Package Quantity	10

Material and Specifications

Material	Vinyl
Material Shortcut	Vinyl
Adhesive	Acrylic
Shortcut Adhesive	Acryl

Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Halogenfree	Yes
Operating Temperature	-40 °F to +180 °F (-40 °C to +82 °C)
ROHS Conformity	Yes
UL Recognized (US)	Yes