# HellermannTyton

## 596-00672



Article Number: 596-00672

Solar Label, Caution - Solar Electric System Connected Reflective Label, 6.5" X 1.0", Yellow, 10/pkg

RoHS

#### **Base Data**

Local Order Number 596-00672

Type CSESC10

Color Yellow (YE)

Features and Benefits • Made with UV stable inks and materials for durability and weather resistance.

• The labels are supplied with aggressive adhesive to ensure long life.

• Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability

to pass inspections.

Color of Print Black (BK)

Product Description HellemannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National

Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer

when variable voltage or series data must be printed and displayed.

Technical Description 6.5" X1" Black text on a yellow background that reads as: "CAUTION - SOLAR ELECTRIC SYSTEM CONNECTED"

in 3/8" tall characters using reflective inks. 10 per pkg.

Short Description Solar Label, Caution - Solar Electric System Connected Reflective Label, 6.5" X1.0", Yellow, 10/pkg

#### **Product Dimensions**

Width W (imperial) 6.5"

Width W (metric) 165.1 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

### Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 10

Package Quantity 10

## **Material and Specifications**

Material Vinyl

Material Shortcut Vinyl

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +302 °F (-40 °C to +150 °C)

Halogenfree Yes

**Operating Temperature**  $-40 \,^{\circ}\text{F} \text{ to } +180 \,^{\circ}\text{F} \text{ (-}40 \,^{\circ}\text{C to } +82 \,^{\circ}\text{C)}$ 

ROHS Conformity Yes
UL Recognized (US) Yes

© HellermannTyton 2014