



Article Number: 596-00677

Solar Label, Photovoltaic System with Rapid Shutdown Reflective Label, 5.5" X 1.75", Red, 10/pkg



Base Data

Local Order Number	596-00677
Type	PSEWRS10
Color	Yellow (YE)
Features and Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance.• The labels are supplied with aggressive adhesive to ensure long life.• Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Color of Print	White (WH)
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	5.5" X 1.75" White text on red background that reads as: "PHOTOVOLTAIC SYSTEM WITH RAPID SHUTDOWN." in 3/8" tall characters. 10 per pkg.
Short Description	Solar Label, Photovoltaic System with Rapid Shutdown Reflective Label, 5.5" X 1.75", Red, 10/pkg

Product Dimensions

Width W (imperial)	5.5 "
Width W (metric)	139.7 mm
Height H (imperial)	1.75 "
Height H (metric)	44.45 mm

Logistics and Packaging

Quantity per	pack
Package Quantity (imperial)	10
Package Quantity	10

Material and Specifications

Material	Vinyl
Material Shortcut	Vinyl
Adhesive	Acrylic
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Halogenfree	Yes
Operating Temperature	-40 °F to +180 °F (-40 °C to +82 °C)

ROHS Conformity Yes

UL Recognized (US) Yes